



TECHNICAL SPECIFICATIONS



EKO FARM 15W-40 Multipurpose (STOU) tractor lubricant

DESCRIPTION

EKO FARM 15W-40 is a multipurpose, Super Tractor Oil Universal (STOU) type lubricant, developed for the lubrication of engines, hydraulic systems, transmissions, differentials and oil-immersed brakes on tractors and farming equipment. EKO FARM 15W40 allows use of the same lubricant for all points of lubrication.

SPECIFICATIONS

API CF-4/SF, ACEA-E3, API GL-4, ZF TE ML 06B/07B, FORD M2C 159B, FORD M2C 134D, JOHN DEERE J20C, NEW HOLLAND 82009201/2/3, CASE NEW HOLLAND MAT 3525 AND 3526, MASSEY FERGUSON CMS M1144 AND 1139, MASSEY FERGUSON CMS M 1143 AND 1145.

APPLICATIONS

- Turbocharged and naturally aspirated diesel engines and gasoline engines.
- Transmission systems with integral final drive, hydraulics and oil immersed brakes.

BENEFITS

- Very good thermal and oxidation stability which reduces sludge build-up and deposits resulting in longer oil and equipment life.
- Effective rust and corrosion protection, which minimizes component wear.
- High TBN value, and TBN retention capability, which reduce deposits formation and extend engine and oil life.
- Very good frictional properties and load carrying capability, which improves hydraulic and transmission system performance and reduces chatter of wet brakes.
- Offers multifunctional service, simplifying lubricants inventory.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,

Tel. + 30 210 5509 511, +30 210 7725 418.

For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO FARM 15W-40 Multipurpose (STOU) tractor lubricant

TYPICAL PROPERTIES

Properties	Methods	Units	EKO FARM 15W-40
SAE Classification	-	-	15W-40
Viscosity @100°C	ASTM D 445	cSt	13,8
Viscosity @40°C	ASTM D 445	cSt	102,4
Viscosity Index (VI)	ASTM D 2270	-	135
Density at 15°C	ASTM D 4052	g/ml	0,884
Sulfated ash	ASTM D 874	% w/w	1,5
Total Base Number (TBN)	ASTM D 2896	mg KOH/gr	10,6
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	232

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.