



TECHNICAL SPECIFICATIONS

EKO GEOTRON 10W, 20W, 30, 40

Multipurpose monograde lubricants

DESCRIPTION

EKO GEOTRON series oils are multipurpose, monograde lubricants which are available in SAE 10W, SAE 20W, SAE 30 and SAE 40 viscosity grades.

SPECIFICATIONS

API SF/CF

APPLICATIONS

- In farming equipment and in light duty applications in construction, mining and quarrying
- In older technology vehicles, where manufacturer suggests API SF or API CF monograde lubricants.

BENEFITS

- Good protection against rust and corrosion.
- Increased resistance to oxidation and thermal degradation.
- High detergency and dispersancy.

Tel. + 30 210 5509 511, +30 210 7725 418.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,

For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.





TECHNICAL SPECIFICATIONS

EKO GEOTRON 10W, 20W, 30, 40 Multipurpose monograde lubricants

TYPICAL PROPERTIES

Properties	Methods	Units	GEOTRON 10W	GEOTRON 20W	GEOTRON 30	GEOTRON 40
SAE Classification	-	-	10W	20W	30	40
Viscosity @100°C	ASTM D 445	cSt	5,9	7,3	11,6	12,6
Viscosity @40°C	ASTM D 445	cSt	36,6	51,0	100,6	118,6
Viscosity Index (VI)	ASTM D 2270	-	105	103	103	97
Density @ 15°C	ASTM D 4052	g/ml	0,883	0,886	0,892	0,895
Pour Point	ASTM D 5950	°C	-27	-27	-27	-27
Flash Point	ASTM D 92	°C	220	224	226	226
Total Base Number (TBN)	ASTM D 2896	mg KOH/gr	6,4	6,4	6,4	6,4

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,

Tel. + 30 210 5509 511, +30 210 7725 418.

For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,

Tel. + 30 210 5509 511, +30 210 7725 418.

For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.