



TECHNICAL SPECIFICATIONS



EKO MEGATRON SUPER SAE 20W-50 Passenger vehicle engine oil

DESCRIPTION

EKO MEGATRON SUPER 20W-50 is a high quality engine lubricant developed for passenger car gasoline and diesel engines and for light truck diesel engines, where manufacturer recommends ACEA A3/B3, API SL/CF or earlier specifications.

It is suitable for use in older generation gasoline engines using LPG as an alternative fuel.

EKO MEGATRON SUPER 20W-50 is highly recommended for engines with many miles of operation.

SPECIFICATIONS

ACEA A3/B3, API SL/CF, MB 229.1

APPLICATIONS

EKO MEGATRON SUPER SAE 20W-50 is suitable for both gasoline and diesel engines, always in accordance with manufacturers' recommendations. Applications include passenger cars, light trucks, SUVs and vans.

BENEFITS

- The SAE 20W50 viscosity grade provides perfect performance in warm atmospheres.
- Offers increased high temperature protection and keeps engine clean.
- Suitable for all type of engines with many miles of operation.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO MEGATRON SUPER SAE 20W-50 Passenger vehicle engine oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON SUPER SAE 20W-50
SAE Classification	-	-	20W-50
Viscosity @100°C	ASTM D 445	cSt	18,5
Viscosity @40°C	ASTM D 445	cSt	168
Viscosity Index (VI)	ASTM D 2270	-	123
Density @ 15°C	ASTM D 4052	g/ml	0,892
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	234

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.