



TECHNICAL SPECIFICATIONS



EKO MEGATRON SUPER DIESEL SAE 15W-40

Passenger vehicle engine oil

DESCRIPTION

EKO MEGATRON SUPER DIESEL 15W-40 is a premium quality engine oil specially developed for modern, high performance passenger car and light truck diesel engines.

EKO MEGATRON SUPER DIESEL 15W-40 is also suitable for gasoline engines, where manufacturer suggests ACEA A3/B4 or API SL quality level.

SPECIFICATIONS

ACEA A3/B3/B4, API SL/CF, MB 229.1, VW 501 01/505 00.

APPLICATIONS

Applications include diesel engines found in passenger cars, light trucks, SUVs and vans, but also gasoline engines, always in accordance with manufacturers' recommendations. EKO MEGATRON SUPER DIESEL 15W-40 is suitable for vehicles of all European and American manufacturers, where ACEA A3/B4 or API SL/CF quality level is required.

BENEFITS

- EKO MEGATRON SUPER DIESEL 15W-40 shows excellent thermal and oxidation stability, so it drastically reduces deposits and sludge build-up, maintaining maximum engine cleanliness and efficiency.
- Provides excellent low and high temperature performance.
- Provides sufficient protection even on extended oil-drain intervals.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO MEGATRON SUPER DIESEL SAE 15W-40 Passenger vehicle engine oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON SUPER DIESEL SAE 15W-40
SAE Classification	-	-	15W-40
Viscosity @100°C	ASTM D 445	cSt	12,94
Viscosity @40°C	ASTM D 445	cSt	92,86
Viscosity Index (VI)	ASTM D 2270	-	137
Sulfated Ash	ASTM D 874	% w/w	1,19
Density @ 15°C	ASTM D 4052	g/ml	0,887
Pour Point	ASTM D 5950	°C	-33
Flash Point	ASTM D 92	°C	230

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.