



TECHNICAL SPECIFICATIONS



EKO MEGATRON SYNTHETIC SAE 5W-40 Passenger vehicle engine oil

DESCRIPTION

EKO MEGATRON SYNTHETIC 5W-40 is a fully synthetic engine oil developed for modern, passenger car and light truck engines.

It is suitable for all types of gasoline and diesel engines with 3-8 years of operation (with the exception of those equipped with diesel particulate filters), where manufacturer recommends SAE 5W-40 viscosity grade and ACEA A3/B4, API SN/CF or earlier specifications.

Due to its high oxidation stability, EKO MEGATRON SYNTHETIC 5W-40 is also suitable for the lubrication of LPG/CNG engines.

SPECIFICATIONS

ACEA A3/B3/B4, API SN/CF, "MB-Approval 229.3", RENAULT RN 0700/RN 0710, VW 502 00/505 00, PORSCHE A40, OPEL GM-LL-A-025, GM-LL-B-025.

APPLICATIONS

EKO MEGATRON SYNTHETIC 5W-40 is suitable for gasoline and diesel engines in modern vehicles of all makes (including MERCEDES BENZ, PORSCHE, OPEL, RENAULT and VOLKSWAGEN), where manufacturer recommends full SAPS engine oil of ACEA A3/B4, API SN/CF or earlier specifications.

BENEFITS

- Superior wear and corrosion protection, which significantly increases engine life.
- Excellent oxidation and thermal stability, which reduces deposits and sludge build-up and prevents viscosity increase, promoting longer engine and oil life.
- Outstanding high and low temperature performance even at the most extended oil drain intervals.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO MEGATRON SYNTHETIC SAE 5W-40 Passenger vehicle engine oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON SYNTHETIC SAE 5W-40
SAE Classification	-	-	5W-40
Viscosity @100°C	ASTM D 445	cSt	15,0
Viscosity @40°C	ASTM D 445	cSt	93,40
Viscosity Index (VI)	ASTM D 2270	-	169
Sulfated Ash	ASTM D 874	% w/w	1,2
Density @ 15°C	ASTM D 4052	g/ml	0,857
Pour Point	ASTM D 5950	°C	-39
Flash Point	ASTM D 92	°C	220

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.