

TECHNICAL SPECIFICATIONS



EKO MEGATRON ULTRA SAE 10W-40

Passenger vehicle engine oil

DESCRIPTION

EKO MEGATRON ULTRA 10W-40 is a premium, semi-synthetic engine oil for passenger car and light truck engines. It is suitable for gasoline and diesel engines, where manufacturer recommends ACEA A3/B4, API SL/ CF or earlier specification, SAE 10W-40 engine oil.

EKO MEGATRON ULTRA 10W-40 is also suitable for the lubrication of LPG / CNG engines and for gasoline engines using LPG as an alternative fuel.

SPECIFICATIONS

ACEA A3/B3/B4, API SL/CF, MB 229.1, VW 501 01/505 00.

APPLICATIONS

EKO MEGATRON ULTRA 10W-40 is suitable for gasoline and diesel passenger cars, light trucks, SUVs and vans, , according to manufacturers' recommendations. It exhibits the same excellent performance in

BENEFITS

- Its semi-synthetic formulation provides higher level of protection compared to mineral oils.
- Provides enhanced low and high temperature performance in both highway and stop and go city driving.
- Reduces deposits and sludge build-up, keeping engine clean and promoting longer engine and oil life.



TECHNICAL SPECIFICATIONS



EKO MEGATRON ULTRA SAE 10W-40

Passenger vehicle engine oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON ULTRA SAE 10W-40
SAE Classification	-	-	10W-40
Viscosity @100°C	ASTM D 445	cSt	14,5
Viscosity @40°C	ASTM D 445	cSt	93,6
Viscosity Index (VI)	ASTM D 2270	-	161
Sulfated Ash	ASTM D 874	% w/w	1,1
Density @ 15°C	ASTM D 4052	g/ml	0,883
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	220

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.