



## TECHNICAL SPECIFICATIONS



### **EKO MOTO RACING SYNTHETIC 4T SAE 10W-40** Fully synthetic engine oil for 4- stroke motorcycles

#### **DESCRIPTION**

EKO MOTO RACING SYNTHETIC 4T 10W-40 is a top tier, fully synthetic engine oil, specially developed for the latest generation of 4-stroke motorcycle engines and particularly for motorcycles racing type.

EKO MOTO RACING SYNTHETIC 4T 10W-40 offers optimum protection to engine and gearbox and superior clutch performance.

#### **SPECIFICATIONS**

API SL, JASO MA2

#### **APPLICATIONS**

- EKO MOTO RACING SYNTHETIC 4T SAE 10W-40 exceeds the requirements of all leading European and Japanese manufacturers and is suitable for virtually all four-stroke motorcycle and scooter engines.
- Suitable for motorcycles with engine, gearbox and wet clutch in one system.

#### **BENEFITS**

- 100% synthetic lubricant, offers immediate acceleration and maximum engine performance in driving in or out of competition.
- Ultimate protection to engines, gearboxes and smooth sliding of clutch discs even under extreme operating conditions.
- Reduced lubricant consumption and superior shear stability which improve oil lifetime.
- Exceptional oxidation and corrosion protection leads to increased oil and engine life.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



## TECHNICAL SPECIFICATIONS



### EKO MOTO RACING SYNTHETIC 4T SAE 10W-40 Fully synthetic engine oil for 4- stroke motorcycles

#### TYPICAL PROPERTIES

Properties	Methods	Units	EKO MOTO RACING SYNTHETIC 4T SAE 10W-40
SAE Classification	-	-	10W-40
Viscosity @100°C	ASTM D 445	cSt	14,9
Viscosity @40°C	ASTM D 445	cSt	99,0
Viscosity Index (VI)	ASTM D 2270	-	160
Density @ 15°C	ASTM D 4052	g/ml	0,86
Sulfated Ash	ASTM D 874	% w/w	1,1
TBN	ASTM D2896	mg KOH/g	7,5
Pour Point	ASTM D 5950	°C	-33

#### HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.