



## TECHNICAL SPECIFICATIONS



### EKO MOTO SUPER 2T

Mineral lubricant for 2-stroke motorcycles and other 2-stroke applications

#### DESCRIPTION

EKO MOTO SUPER 2T is a low ash mineral lubricant, designed for 2-stroke motorcycle and scooter engines. It is also suitable for snowmobiles, lawn mowers and chainsaws.

#### SPECIFICATIONS

JASO FB, ISO-L-EGB

#### APPLICATIONS

EKO MOTO SUPER 2T is suitable for both premix (fuel:oil ratio up to 50:1, according to manufacturers' recommendations), and oil injection systems.

EKO MOTO SUPER 2T is pre-diluted, to facilitate mixing when added to fuel.

#### BENEFITS

- Due to its low ash formulation, EKO MOTO SUPER 2T protects against pre-ignition while at the same time ensures cleanliness and reliable operation of the engine.
- Protects against wear, rust and corrosion.



## TECHNICAL SPECIFICATIONS



### EKO MOTO SUPER 2T

Mineral lubricant for 2-stroke motorcycles and other 2-stroke applications

#### TYPICAL PROPERTIES

Properties	Methods	Units	EKO MOTO SUPER 2T
Color	VISUAL	-	Red
Viscosity @100°C	ASTM D 445	cSt	7,8
Density @ 15°C	ASTM D 4052	g/ml	0,88
Sulfated Ash, max	ASTM D 874	% w/w	0,06
TBN	ASTM D2896	mg KOH/g	0,56
Pour Point	ASTM D 5950	°C	-27
Flash Point	ASTM D 93	°C	120

#### HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.