



## TECHNICAL SPECIFICATIONS



### EKO MOTO SUPER 4T SAE 20W-50 Engine oil for 4-stroke motorcycles

#### DESCRIPTION

EKO MOTO SUPER 4T 20W-50 is a 4-stroke motorcycle and scooter engine oil, developed for maximum all year protection and efficient lubrication over a wide temperature range.

#### SPECIFICATIONS

API SG, JASO MA

#### APPLICATIONS

EKO MOTO SUPER 4T 20W-50 is developed for transport and day-to-day riding during all seasons.

EKO MOTO SUPER 4T 20W-50 is recommended where manufacturer suggests JASO MA and API SG quality level.

#### BENEFITS

- Formulated to provide year-round protection and sufficient lubrication over a wide temperature range.
- Provides good lubrication in normal service conditions.
- The SAE 20W50 viscosity grade offers excellent performance in warm atmospheres.
- Offers sufficient protection to engines and gearboxes and good clutch performance.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



## TECHNICAL SPECIFICATIONS



### EKO MOTO SUPER 4T SAE 20W-50 Engine oil for 4-stroke motorcycles

#### TYPICAL PROPERTIES

Properties	Methods	Units	EKO MOTO SUPER 4T 20W-50
SAE Classification	-	-	20W-50
Viscosity @100°C	ASTM D 445	cSt	19,5
Viscosity @40°C	ASTM D 445	cSt	172,1
Viscosity Index (VI)	ASTM D 2270	-	130
TBN	ASTM D 2896	mg KOH/g	8,1
Sulfated Ash	ASTM D 874	% w/w	1,2
Density @ 15°C	ASTM D 4052	g/ml	0,892
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	230

#### HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.