

#### **TECHNICAL SPECIFICATIONS**



# **EKOGREASE LC 2**

Multipurpose calcium thickened grease

### **DESCRIPTION**

EKOGREASE LC 2 is a calcium thickened multipurpose grease which ensures excellent water wash-out resistance and very good adhesion to metal surfaces.

EKOGREASE LC 2 is suitable for various general lubrication applications at operating temperatures from -30°C to +80°C, where low or moderate loads are involved.

### **SPECIFICATIONS**

DIN 51825 K3E-30

### **APPLICATIONS**

EKOGREASE LC 2 is suitable for a wide range of applications including the lubrication of chassis in vehicles and agricultural equipment, for applications where there is contact with water and for bearings operating under low or moderate load conditions, in a temperature range from -30°C to +80°C.

### **BENEFITS**

- Very good water wash-out resistance and protection against rust and corrosion.
- Good mechanical stability and low temperature pumpability.
- Excellent adhesion to metal surfaces.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support.



### **TECHNICAL SPECIFICATIONS**



# **EKOGREASE LC 2**

Multipurpose calcium thickened grease

### **TYPICAL PROPERTIES**

Property	Method	Unit	EKOGREASE LC 2
NLGI Grade	ASTM D 217	-	2
Color		Visual	amber
Dropping point	ASTM D 566	°C	95
Penetration (60strokes), @ 25° C	ASTM D 217	mm-1	265-295
Temperature range	-	°C	-30°C to +80°C

# **HYGIENE AND SAFETY**

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.