



PRODUCT DATA SHEET



EKO AERO EP

Lubricants for pneumatic equipment

DESCRIPTION

The EKO AERO EP lubricant series includes high performance lubricants specifically designed for the lubrication of rock drills and pneumatic tools.

EKO AERO EP lubricants exhibit excellent adhesive and emulsifying properties, and do not cause sludge build-up that could slow down valve movement. These properties, combined with the excellent EP characteristics of the EKO Aero EP series lubricants, help provide optimal lubrication and prolong the life of equipment.

APPLICATIONS

- Underground and aboveground applications in mines, and applications in industry and construction.
- EKO AERO EP 46 is chiefly recommended for use in lightweight air tools and drills during winter months.
- EKO AERO EP 100 is suitable for medium and heavy-duty applications in mining and construction.
- EKO AERO EP 150 is recommended for use all year round in applications operating in high temperatures.

ADVANTAGES

- Excellent resistance to oxidation and sludge build-up.
- Very good adhesion characteristics.
- Effective lubrication in the presence of moisture.
- Excellent protection against rust and corrosion in the presence of moisture.
- Excellent protection of tools against wear.
- Minimizes oil mist formation, ensuring a safer working environment.



PRODUCT DATA SHEET

TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO AERO EP 46	EKO AERO EP 68	EKO AERO EP 100	EKO AERO EP 150
ISO Viscosity Grade	-	-	46	68	100	150
Density at 15°C	ASTM D 4052	g/ml	0.878	0.880	0.888	0.890
Kinematic viscosity at 100°C	ASTM D 445	cSt	6.7	8.6	11.1	14.5
Kinematic viscosity at 40°C	ASTM D 445	cSt	46	68	100	150
Viscosity Index (VI)	ASTM D 2270	-	99	98	96	96
Pour Point	ASTM D 5950	°C	-24	-24	-21	-18
Flash Point	ASTM D 92	°C	230	240	250	260

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 2, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.