



## PRODUCT DATA SHEET

### EKO BRAKE FLUID SUPER DOT 4 brake fluid

#### DESCRIPTION

EKO BRAKE FLUID SUPER is a high-quality brake fluid for hydraulic brake systems and clutches, with a boiling point of at least 265°C and a wet boiling point of at least 170°C.

EKO BRAKE FLUID SUPER is made of glycols, glycol ethers and glycol ether borates, and contains oxidation and corrosion inhibitors.

#### SPECIFICATIONS

SAE J 1704, SAE J 1703, FMVSS 116 DOT 3 και DOT 4, ISO 4925 Class 4.

#### Suitable for use

VW/Audi/Seat/Skoda TL 766-X, Ford SA-M6C9103-A, MAN FMVSS 116 DOT 4, Toyota TSK2602G.

#### APPLICATIONS

- It is suitable for use in new- and old-technology cars and commercial vehicles requiring DOT 4 or DOT 3 level brake fluid.
- Especially recommended for braking systems equipped with ABS, ASC and ESP.

#### ADVANTAGES

- High boiling point: ensures the stable and safe operation of brakes even under difficult braking conditions.
- High thermal and oxidative stability and excellent corrosion protection: it extends the life and reliability of brake system components.
- Compatible with elastomers: it minimizes leakage and fluid loss.



## PRODUCT DATA SHEET

### TYPICAL CHARACTERISTICS

Properties	Units	EKO BRAKE FLUID SUPER
Appearance	Visual inspection	Yellow liquid, free of mineral oil and insoluble substances
Density, 20°C	g/ml	1.06
Chemical stability	°C	+/- 5
Thermal stability	°C	+/- 5
Viscosity, -40°C, max	cSt	900-1100
Viscosity, 100°C, min	cSt	1.5
Boiling point	°C	265
Wet Boiling point	°C	170
pH	-	8.0-9.0
Water content, max	% wt	0.2

### SPECIAL INSTRUCTIONS

Follow the manufacturer's instructions when adding brake fluid. Keep the brake fluid clean and dry. Only store the brake fluid in its original packaging container. Keep the container clean and hermetically sealed to prevent the absorption of moisture. CAUTION! Do not refill the container or use it for other liquids.

**Shelf life:** At least five years under proper storage conditions (in original containers sealed and at temperatures of up to 40°C).

Issue 9, 31 October 2022

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511. Advice on safe handling is provided in the Safety Data Sheet.