



PRODUCT DATA SHEET



EKO FORZA PREMIUM 20W-50 Lubricant for commercial vehicle engines

DESCRIPTION

EKO FORZA PREMIUM 20W-50 is an exceptionally high-performance lubricant, especially designed to protect and keep the engine clean at extended oil drain intervals. Suitable for modern diesel engines operating on and off road in demanding conditions.

SPECIFICATIONS

ACEA E7, API CI-4, API CF/SL, MB 228.3, MAN M3275, CATERPILLAR ECF-1a, GLOBAL DHD-1.

APPLICATIONS

- Heavy-duty, naturally aspirated and turbocharged diesel engines.
- On and off-highway applications.
- Meets the requirements of all major manufacturers allowing for the use of one lubricant for mixed fleets of commercial vehicles and earthmoving equipment of different manufacturers.

ADVANTAGES

- Powerful lubricating membrane at high temperatures.
- Excellent anti-wear protection and deposit control.
- Maximum anti-corrosion protection.
- Bore polish prevention.
- High dispersion of soot in lubricant.
- Suitable for extended oil drain intervals.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO FORZA PREMIUM 20W-50
SAE Viscosity Grade	-	-	20W-50
Kinematic Viscosity at 100°C	ASTM D 445	cSt	18.5
Kinematic Viscosity at 40°C	ASTM D 445	cSt	165.1
Viscosity Index (VI)	ASTM D 2270	-	126
Density at 15°C	ASTM D 4052	g/ml	0.894
Sulfated Ash	ASTM D 874	% w/w	1.4
Base number, TBN	ASTM D2896	mg KOH/g	10.4
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	240

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 4, 17 September 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.