



PRODUCT DATA SHEET



EKO MEGATRON SUPER 15W-40 Lubricant for passenger vehicle engines

DESCRIPTION

EKO MEGATRON SUPER 15W-40 is a synthetic technology lubricant, suitable for gasoline and diesel engines of passenger vehicles and light trucks.

EKO MEGATRON SUPER 15W-40 is mainly recommended for normal change intervals for old generation vehicles with several kilometres of operation.

SPECIFICATIONS

ACEA A3/B3, API SL/CF, MB 229.1.

APPLICATIONS

- It is suitable for gasoline engines and diesel engines without diesel particulate filters (DPF), where manufacturers recommend ACEA A3/B3 lubricants.
- It is suitable for MERCEDES engines for which an MB 229.1 lubricant is recommended.
- It is suitable for LPG and CNG engines.

ADVANTAGES

- Protection and cleanliness of the engine under normal driving conditions.
- Excellent fluidity of the lubricant during engine start, leading to satisfactory lubrication and sufficient protection of all mechanical parts.
- Oxidation and thermal degradation resistant leading to reduction of deposits and increase of both the lubricant's as well as of the engine's service life.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MEGATRON SUPER 15W-40
SAE Viscosity Grade	-	-	15W-40
Density at 15°C	ASTM D 4052	g/ml	0.882
Kinematic Viscosity at 100°C	ASTM D 445	cSt	13.88
Kinematic viscosity at 40°C	ASTM D 445	cSt	103.0
Viscosity Index (VI)	ASTM D 2270	-	135
Base number, TBN	ASTM D 2896	mg KOH/g	8.2
CCS Viscosity at -20°C	ASTM D 5293	cP	6500
Pour point	ASTM D 5950	°C	-30
Flash point	ASTM D 92	°C	228

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze and water, to allow for proper handling.

Issue 6, 13 September 2019

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.