



PRODUCT DATA SHEET



EKO MEGATRON SUPER 20W-50 Lubricant for passenger vehicle engines

DESCRIPTION

EKO MEGATRON SUPER 20W-50 is a synthetic technology lubricant, designed for gasoline and diesel engines of passenger vehicles and light trucks.

EKO MEGATRON SUPER 20W-50 is recommended for normal change intervals in vehicles of past technology with significant amount of kilometres run.

SPECIFICATIONS

ACEA A3/B3, API SL/CF, MB 229.1.

APPLICATIONS

- It is suitable for passenger cars and light trucks.
- It is suitable for gasoline engines and diesel engines without diesel particulate filters (DPF), where the manufacturer recommends ACEA A3/B3 lubricants.
- It is suitable for daily driving under normal conditions.
- It is suitable for CNG and LPG engines.

ADVANTAGES

- Strong lubricant membrane in high temperatures.
- Increased cleanliness and engine protection.
- Excellent wear protection.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MEGATRON SUPER 20W-50
SAE Viscosity Grade	-	-	20W-50
Density at 15°C	ASTM D 4052	g/ml	0.888
Kinematic viscosity at 100°C	ASTM D 445	cSt	18.08
Kinematic viscosity at 40°C	ASTM D 445	cSt	164.4
Viscosity index (VI)	ASTM D 2270	-	122
Base number, TBN	ASTM D 2896	mg KOH/g	8.2
CCS viscosity at -15°C	ASTM D 5293	cP	8080
Pour point	ASTM D 5950	°C	-30
Flash point	ASTM D 92	°C	248

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze and water, to allow for proper handling.

Issue 5, 13 September 2019

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.