



PRODUCT DATA SHEET



EKO MEGATRON SUPER DIESEL 15W-40 Lubricant for passenger vehicle engines

DESCRIPTION

EKO MEGATRON SUPER DIESEL 15W-40 is an advanced, mineral based lubricant, suitable for all modern diesel engines for passenger vehicles and light trucks, for which manufacturers recommend a <full SAPS> lubricant.

SPECIFICATIONS

ACEA A3/B4, ACEA A3/B3, API SL/CF, MB 229.1, VW 501 01/505 00.

APPLICATIONS

- Specifically designed for modern, direct injection diesel engines without diesel particulate filters (DPF), for which manufacturers recommend ACEA A3/B4 quality lubricants.
- Suitable also for gasoline engines for which manufacturers recommend a lubricant of a respective quality level.

ADVANTAGES

- Reduces deposits thus providing maximum cleanliness and high engine performance.
- Provides excellent protection against wear under high or low temperature conditions.
- Ensures long change intervals.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MEGATRON SUPER DIESEL 15W-40
SAE Viscosity grade	-	-	15W-40
Density at 15°C	ASTM D 4052	g/ml	0.887
Kinematic viscosity at 100°C	ASTM D 445	cSt	12.94
Kinematic viscosity at 40°C	ASTM D 445	cSt	92.86
Viscosity index (VI)	ASTM D 2270	-	137
Sulfated ash	ASTM D 874	% w/w	1.19
CCS viscosity at -20°C	ASTM D 5293	cP	6600
Pour point	ASTM D 5950	°C	-33
Flash point	ASTM D 92	°C	230

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze and water, to allow for proper handling.

Issue 4, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.