



PRODUCT DATA SHEET



EKO MEGATRON ULTRA DIESEL 10W-40 Lubricant for passenger vehicle engines

DESCRIPTION

EKO MEGATRON ULTRA DIESEL 10W-40 is an advanced, synthetic technology, high performance lubricant, suitable for all modern diesel engines of passenger cars and light trucks for which manufacturers recommend <full SAPS> lubricant with ACEA A3/B4 quality level and SAE 10W-40 viscosity grade.

SPECIFICATIONS

ACEA A3/B4, ACEA A3/B3, API SL/CF, MB 229.1, VW 501 01/505 00.

APPLICATIONS

- Modern, direct injection diesel engines as well as older diesel engines of all manufacturers, where a <full SAPS> lubricant with SAE 10W-40 viscosity grade is recommended.
- It is also suitable for gasoline engines when manufacturers recommend a lubricant of the specific quality level.

ADVANTAGES

- Reduces deposits, thus ensuring maximum cleanliness and engine performance.
- Provides engine protection in high and low temperatures.
- It is suitable for prolonged change intervals.



PRODUCT DATA SHEET

TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MEGATRON ULTRA DIESEL 10W-40
SAE Viscosity Grade	-	-	10W-40
Density at 15°C	ASTM D 4052	g/ml	0.874
Kinematic viscosity at 100°C	ASTM D 445	cSt	13.65
Kinematic viscosity at 40°C	ASTM D 445	cSt	90.83
Viscosity index (VI)	ASTM D 2270	-	153
Sulfated ash	ASTM D 874	% w/w	1.25
CCS viscosity at -25°C	ASTM D 5293	cP	6600
Pour point	ASTM D 5950	°C	-36
Flash point	ASTM D 92	°C	228

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze and water, to allow for proper handling.

Issue 3, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.