



PRODUCT DATA SHEET



EKO MOTO RACING SYNTHETIC 4T 10W-40 Lubricant for four-stroke motorcycles

DESCRIPTION

EKO MOTO RACING SYNTHETIC 4T 10W-40 is a top-of-the-line full synthetic lubricant, specially designed for last-generation high-performance 4-stroke motorcycle engines.

It is also suitable for racing engines.

It provides excellent protection for engine and gearbox, optimal clutch efficiency and unique performance on both racetracks and day-to-day riding.

SPECIFICATIONS

API SL, JASO MA2.

APPLICATIONS

- It exceeds the requirements of all European and Japanese four-stroke motorcycle manufacturers.
- It is suitable for all modern four-stroke motorcycle and scooter engines.

ADVANTAGES

- Maximized acceleration and engine performance.
- Excellent protection at high speeds and high temperatures.
- Exceptional viscosity characteristics that ensure effective lubrication when starting the engine.
- Excellent protection for engine, clutch and gearbox.
- Also suitable for motorcycles with catalytic converters.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MOTO RACING SYNTHETIC 4T 10W-40
SAE Viscosity Grade	-	-	10W-40
Kinematic viscosity at 100°C	ASTM D 445	cSt	14.9
Kinematic viscosity at 40°C	ASTM D 445	cSt	99.0
Viscosity Index	ASTM D2270	-	160
Density at 15°C	ASTM D 4052	g/ml	0.86
Sulfated ash	ASTM D 874	% w/w	1.1
Base number, TBN	ASTM D 2896	mg KOH/g	7.5
Pour Point	ASTM D 5950	°C	-33

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 2, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.