



## PRODUCT DATA SHEET



### EKO MOTO SUPER 2T

Lubricant for two-stroke motorcycles and other two-stroke engine applications

#### DESCRIPTION

EKO MOTO SUPER 2T lubricant is a low ash mineral oil designed for two-stroke motorcycles and scooters. It is also suitable for snowmobiles, lawn mowers and chainsaws.

#### SPECIFICATIONS

JASO FB, ISO-L-EGB.

#### APPLICATIONS

- EKO MOTO SUPER 2T is suitable for oil injection and pre-mix systems.
- The fuel/lubricant ratio in pre-mix systems is up to 50:1, always according to the manufacturer's instructions.

#### ADVANTAGES

- It lubricates critical engine parts and minimizes wear.
- It ensures adequate pre-ignition protection and a cleaner engine.
- It decreases deposits on cylinder and springs, resulting in increased engine performance.
- It effectively protects the engine from corrosion and rust.
- It is pre-diluted to facilitate mixing when added to the fuel.



## PRODUCT DATA SHEET



### TYPICAL CHARACTERISTICS

| Properties                   | Methods           | Units    | EKO MOTO SUPER 2T |
|------------------------------|-------------------|----------|-------------------|
| SAE Viscosity Grade          | -                 | -        | 20                |
| Colour                       | Visual inspection | -        | Red               |
| Kinematic viscosity at 100°C | ASTM D 445        | cSt      | 7.8               |
| Density at 15°C              | ASTM D 4052       | g/ml     | 0.88              |
| Sulfated ash                 | ASTM D 874        | % w/w    | 0.06              |
| Base number, TBN             | ASTM D 2896       | mg KOH/g | 0.56              |
| Pour Point                   | ASTM D 5950       | °C       | -27               |
| Flash point, min             | ASTM D 92         | °C       | 150               |

### HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 3, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.