



## PRODUCT DATA SHEET



### **EKO MOTO SUPER 4T 20W-50** Lubricant for four-stroke motorcycles

#### **DESCRIPTION**

EKO MOTO SUPER 4T 20W-50 is a mineral-based lubricant for four-stroke motorcycle engines, formulated to provide adequate lubrication over a wide range of operating temperatures.

#### **SPECIFICATIONS**

API SG, JASO MA.

#### **APPLICATIONS**

- EKO MOTO SUPER 4T 20W-50 is designed for everyday riding all year round.
- It is suitable for modern four-stroke motorcycle and scooter engines, where JASO MA and API SG quality fluids are recommended by the manufacturer.

#### **ADVANTAGES**

- The SAE 20W-50 viscosity grade of the EKO MOTO SUPER 4T 20W-50 lubricant ensures excellent lubrication in warmer ambient temperatures.
- It provides very good engine and gearbox protection, and excellent clutch performance.
- It ensures year-round protection and efficient lubrication over a wide range of operating temperatures.



## PRODUCT DATA SHEET



### TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MOTO SUPER 4T 20W-50
SAE Viscosity Grade	-	-	20W-50
Kinematic viscosity at 100°C	ASTM D 445	cSt	19.49
Kinematic viscosity at 40°C	ASTM D 445	cSt	172.1
Viscosity Index (VI)	ASTM D 2270	-	130
Base number, TBN	ASTM D 2896	mg KOH/g	8.1
Sulfated ash	ASTM D 874	% w/w	1.2
Density at 15°C	ASTM D 4052	g/ml	0.892
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	230

### HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 3, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.