



PRODUCT DATA SHEET



EKO MOTO ULTRA 4T 10W-40

Lubricant for four-stroke motorcycles

DESCRIPTION

EKO MOTO ULTRA 4T 10W-40 is a synthetic technology lubricant suitable for all types of four-stroke motorcycles and scooters. It provides excellent protection for engine, clutch and gearbox.

SPECIFICATIONS

API SL, JASO MA2.

APPLICATIONS

- The quality level and fluidity of EKO MOTO ULTRA 4T 10W-40, in conjunction with the synthetic lubricant technology used meet the specifications of all current European and Japanese manufacturers of four-stroke motorcycle scooter lubricants.
- Also suitable for motorcycles with catalytic converters.

ADVANTAGES

- Exceptional viscosity characteristics that ensure effective lubrication when starting the engine.
- It ensures maximum engine cleanliness.
- It provides excellent protection for engine, clutch and gearbox.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MOTO ULTRA 10W-40
SAE Viscosity Grade	-	-	10W-40
Kinematic viscosity at 100°C	ASTM D 445	cSt	14.5
Kinematic viscosity at 40°C	ASTM D 445	cSt	93.6
Viscosity Index	ASTM D 2270	-	161
Density at 15°C	ASTM D 4052	g/ml	0.883
Base number, TBN	ASTM D 2896	mg KOH/g	8.1
Pour Point	ASTM D 5950	°C	-30

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 3, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.