



PRODUCT DATA SHEET



EKOGREASE CHASSIS

Semi-fluid lithium grease

DESCRIPTION

EKOGREASE CHASSIS is a high quality lithium grease enhanced with antioxidants, corrosion inhibitors and extreme pressure (EP) additives.

SPECIFICATIONS

DIN 51825 KP00K-30.

APPLICATIONS

- It is recommended for the lubrication of rolling-element bearings and plain bearings in automotive units and agricultural equipment.
- EKOGREASE CHASSIS has an NLGI 00 consistency grade, ensuring its suitability for industrial centralised lubrication systems requiring the use of semi-fluid grease.
- The product is also suitable for gear case lubrication.

ADVANTAGES

- Optimal performance with heavy loads.
- Excellent lubricity and mechanical stability.
- Resistance to washout by water.
- Increased protection against corrosion.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKOGREASE CHASSIS
Soap base	-	-	Lithium
Base oil	-	-	Mineral oil
NLGI	ASTM D217	-	00
Colour	Visual Inspection	-	Amber
Texture	Visual Inspection	-	Smooth / Homogeneous
Worked penetration (60 strokes), 25°C	ASTM D 217	mm ⁻¹	400-430
Base oil viscosity at 40°C	ASTM D 445	cSt	200
Oxidation stability, 100 hrs, Pressure drop	ASTM D 942	psi	5
Roll stability	ASTM D 1831	mm ⁻¹	-25 to +60
Water washout %, max	ASTM D 1264	%	10
Timken OK load test	ASTM D 2509	lbs	>45
4 ball wear test, mm	ASTM D 2266	mm	<0.60
4 ball weld point test	ASTM D 2596	Kg	250
Rust protection	ASTM D 1743	-	pass
Copper corrosion (Cu), max.	ASTM D 4048	-	1b
Operating temperature	-	°C	-30°C to +100°C, max. +110°C

HEALTH AND SAFETY

Protect the environment while disposing of used product.

Issue 3, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. + 30 210 5509511 and + 30 210 7725418. Advice on safe handling is provided in the Safety Data Sheet.