



## PRODUCT DATA SHEET

### EKOGREASE FM 2

Aluminum complex food machinery grease

#### DESCRIPTION

EKOGREASE FM 2 is an aluminum complex grease manufactured with pharmaceutical grade white oils and polymers and enhanced with antioxidants and anti-wear additives (EP/AW).

EKOGREASE FM 2 has been specially designed for use in the food industry.

#### SPECIFICATIONS

DIN 51502 KP2K-20, ISO 12924 L-XB (F) CDB2.

#### APPLICATIONS

- EKOGREASE FM 2 contains aluminum complex soap which, combined with the base fluid's high viscosity, make it ideal for roller bearings operating at low or moderate speeds and carrying heavy loads.
- It may be used to lubricate roller and/or plain bearings, as well as other mechanical parts of food machinery, where there is a possibility of incidental or accidental contact with food.

#### ADVANTAGES

- Good oxidation resistance.
- Excellent heavy-load performance.
- Good resistance to washout by water.
- Suitable for the lubrication of machinery used in the food industry.



## PRODUCT DATA SHEET

### TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKOGREASE FM 2
Soap Base	-	-	Aluminum Complex
Base Fluid	-	-	Pharmaceutical Paraffin White Oils
NLGI	ASTM D217	-	2
Colour	Visual Inspection	-	White
Dropping Point	IP 396	°C	>230
Base oil Viscosity at 40°C	ASTM D7152	cSt	550
Worked Penetration, 60 strokes	ISO 2137	mm <sup>-1</sup>	265-295
Washout Resistance	ISO 11009	%	<10
SKF Emcor dist. water	ISO 11007	-	>1-1
Water Resistance at 90°C	DIN 51807:1	-	0
4-Ball weld load	DIN 51350:5	N	6000
SKF R2F B at 120°C	SKF	-	Pass
Operating Temperature	-	°C	-20°C to +120°C, max. +130°C

### HEALTH AND SAFETY

Protect the environment while disposing of used product.

Issue 4, 31 October 2022

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. + 30 210 5509511.  
Advice on safe handling is provided in the Safety Data Sheet.