



PRODUCT DATA SHEET

EKOGREASE OG Open gear lithium grease

DESCRIPTION

EKOGREASE OG is a high quality lithium grease enhanced with extreme pressure (EP) additives and graphite and specially designed for chains and open gears.

APPLICATIONS

- Heavy load open transmission systems operating at low and/or moderate speeds in heavy-duty operations.
- Suitable for industrial (steel, cement, paper, chemicals) and marine applications, mining, construction.
- Suitable for extremely high temperature operations in environments including humidity and corrosive factors.

SPECIFICATIONS

DIN 51825 KP2K-30.

ADVANTAGES

- Outstanding adhesion, resulting in less grease bleed and therefore reduced product consumption.
- Excellent corrosion and rust protection.
- Enhanced load carrying capacity allowing for improved gear protection against wear.
- Wide operating temperature range.



PRODUCT DATA SHEET

TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKOGREASE OG
Soap Base	-	-	Lithium
Base Oil	-	-	Mineral Oil
NLGI	ASTM D217	-	2
Colour	Visual Inspection	-	Black
Dropping Point	ASTM D566	°C	200
Worked Penetration, 60 strokes	ASTM D217	mm ⁻¹	265-295
Operating Temperature	-	°C	-30°C to +130°C

HEALTH AND SAFETY

Protect the environment while disposing of used product.

Issue 3, 31 October 2022

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511.
Advice on safe handling is provided in the Safety Data Sheet.