



PRODUCT DATA SHEET



EKO FORZA RR 40 Lubricant for commercial vehicle engines

DESCRIPTION

EKO FORZA RR 40 is a high-quality monograde lubricant, especially designed for medium-speed diesel engines for which manufacturers recommend ACEA E2 and API CF quality engine oils.

Also suitable for two-stroke diesel engines with manufacturer recommendation of API CF-2 quality monograde lubricant with SAE 40 viscosity grade.

SPECIFICATIONS

ACEA E2, API CF/CF-2, API SF, MAN 270, MTU Type 1, MB 228.0.

APPLICATIONS

- Medium-speed diesel engines operating in industrial applications, shipping and railways.
- Commercial vehicles of light and medium requirements.
- Two-stroke diesel engines for which the use of API CF-2, SAE 40 is recommended.
- Gasoline engines with manufacturer recommendation of API SF quality level.

ADVANTAGES

- High protection from rust and corrosion.
- Increased resistance to oxidative and thermal breakdown.
- Its high detergent and dispersant capability contributes to the quick and effective removal of carbon deposits and sludge and keeps engine clean.
- High alkalinity (TBN) resulting in high protection from wear caused by the corrosive acids produced at combustion.
- Longer oil drain intervals.



PRODUCT DATA SHEET



TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO FORZA RR 40
SAE Viscosity Grade	-	-	40
Kinematic Viscosity at 100°C	ASTM D 445	cSt	14.0
Kinematic Viscosity at 40°C	ASTM D 445	cSt	134.7
Viscosity Index (VI)	ASTM D 2270	-	101
Density at 15°C	ASTM D 4052	g/ml	0.893
Sulfated Ash	ASTM D 874	% w/w	1.5
Base number, TBN	ASTM D2896	mg KOH/g	11.1
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	250

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 4, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.