



## PRODUCT DATA SHEET



### EKO BASE LUBE 10, 30

General use additive-free mineral oils

#### DESCRIPTION

EKO BASE LUBE 10 and EKO BASE LUBE 30 are additive-free mineral oils.

#### APPLICATIONS

They are suitable for the lubrication of tools, formworks, and for numerous other applications where additive-free mineral oil is recommended.

#### TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO BASE LUBE 10	EKO BASE LUBE 30
Colour	ASTM D 1500	-	L0.5	L1.5
Density at 15°C	ASTM D 4052	g/ml	0.877	0.886
Kinematic viscosity at 100°C	ASTM D 445	cSt	5.3	10.5
Viscosity Index (VI)	ASTM D 2270	cSt	99	95
Pour Point	ASTM D 5950	°C	-12	-6
Flash Point	ASTM D 92	°C	232	250

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.



## PRODUCT DATA SHEET



### HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 4, 3 January 2018

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.