



PRODUCT DATA SHEET



EKO MARINE PREMIUM 15W-40

Lubricant for marine 4-stroke diesel engines

DESCRIPTION

EKO MARINE PREMIUM 15W-40 is an extra high performance multigrade heavy-duty diesel engine oil, suitable for almost all high-speed four-stroke marine diesel engines operating on coastal shipping, fishing, leisure boats and other applications.

EKO MARINE PREMIUM 15W-40 is suitable for modern low-emission marine diesel engines-including engines equipped with exhaust reduction systems such as EGR and SCR systems, but also for older engines.

The formulation of EKO MARINE PREMIUM 15W-40 improves the reliability and the lifespan of the engine and contributes to reducing maintenance costs and fuel costs.

EKO MARINE PREMIUM 15W-40 meets the performance requirements of the major diesel engines manufacturers, including MTU, VOLVO, MAN, CUMMINS, CATERPILLAR, MACK, IVECO, YANMAR, BAUDOUIN, DEUTZ, PERKINS and DETROIT DIESEL.

SPECIFICATIONS

ACEA E7, API CI-4/CH-4/SL/SJ, CAT ECF-2, CAT ECF-1a, CUMMINS CES 20076/20077/20078, DDC 93K215, DEUTZ DQC III-10, GLOBAL DHD-1, JASO DH-1, MACK EO-N/EO-M PLUS/EO-M, MAN M3275-1, MB 228.3, MTU Type 2, RENAULT VI RLD-2, VOLVO VDS-3.

APPLICATIONS

- High-speed propulsion engines, naturally aspirated or turbocharged, operating on coastal vessels, fishing boats, lifeboats and leisure boats.
- High-speed engine generators.
- Transmission systems and auxiliary units, according to manufacturer's recommendations.



PRODUCT DATA SHEET



ADVANTAGES

- Excellent protection against wear: increases the lifespan of all critical engine components.
- Excellent water resistance: helps maintaining a strong lubricating film in the presence of seawater.
- Excellent control of deposits: increases cleanliness and reliability of the engine and reduces lubricant consumption.
- Excellent resistance to thermal degradation: provides lasting protection of the engine at extended oil-drain intervals, even under the most severe operating conditions.
- High TBN value and excellent retention of TBN value: protects all engine components against corrosive wear at extended lubricant-operation intervals.
- High shear stability and high viscosity index: help maintaining a strong lubricating film at all operating temperatures.
- Excellent performance at low temperatures: provide excellent control of wear at the start of the engine.

TYPICAL CHARACTERISTICS

Properties	Methods	Units	EKO MARINE PREMIUM 15W-40
SAE Viscosity Grade	-	-	15W-40
Density, 15°C	ASTM D4052	g/ml	0.885
Kinematic viscosity, 100°C	ASTM D445	cSt	14.50
Kinematic viscosity, 40°C	ASTM D445	cSt	106.1
Viscosity index (VI)	ASTM D2270	-	141
CCS viscosity, -20°C	ASTM D5293	cP	6400
Sulfated Ash	ASTM D874	% w/w	1.3
Base number, TBN	ASTM D2896	mg KOH/g	11.5
Pour Point	ASTM D5950	°C	-36
Flash Point	ASTM D92	°C	230

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 1, 19 May 2020

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.