



PRODUCT DATA SHEET



EKO FORZA FUEL ECONOMY 10W-30 E6/E9

Lubricant for commercial vehicle engines

DESCRIPTION

EKO FORZA FUEL ECONOMY 10W-30 E6/E9 is a synthetic technology lubricant, designed for the highest level of performance in modern low emissions diesel engines operating on and off-highway.

The SAE 10W-30 viscosity grade and the modern technology of the lubricant help fuel saving, compared to SAE 15W-40 and SAE 10W-40 lubricants.

EKO FORZA FUEL ECONOMY 5W-30 E6/E9 meets and exceeds the current specifications ACEA E6-16, E7-16, E9-16, MB 228.51 and other OEM's specifications, which are required for engines meeting the latest EU emission standards Euro 6 and EU stage IV.

EKO FORZA FUEL ECONOMY 10W-30 E6/E9 is particularly recommended for EGR diesel engines fitted with modern exhaust after-treatment systems, such as diesel particulate filters (DPF) and SCR systems.

The formulation of EKO FORZA FUEL ECONOMY 5W-30 E6/E9 provides excellent protection and cleanliness to the engine, thus maximizing performance and increasing its lifespan.

The excellent antioxidant properties of EKO FORZA FUEL ECONOMY 5W-30 E6/E9 contribute to extensive oil-change intervals. Low volatility loss and high resistance to shear provide excellent control of lubricant consumption. The final benefit is the reduction of maintenance costs and operating costs.

EKO FORZA FUEL ECONOMY 5W-30 E6/E9 has excellent fluidity and pumpability characteristics at low temperatures, as demonstrated by the excellent results in the CCS and MRV tests. It thus allows the engine to start easily at low ambient temperatures and minimizes wear at startup.



PRODUCT DATA SHEET



SPECIFICATIONS

ACEA E6/E7/E9, API CK-4/SN, JASO DH-2, MB 228.31, MB 228.51, MB 228.52, MAN M3775, MTU Type 3.1, DEUTZ DQC IV-18 LA, CUMMINS CES 20086, DDC 93K222, CATERPILLAR ECF-3, VOLVO STD 417-0003: VOLVO VDS-4.5, MACK EOS-4.5, RENAULT RLD-3, IVECO 18-1804 TLS E9, DAF Extended drain.

Suitable for use: API CJ-4, API CI-4 plus, API CI-4, API CH-4, API SM, API SL.

APPLICATIONS

- Suitable for high-performance EURO 6 and EU Stage IV diesel engines, but also fully compatible with older diesel engines, in which use of EKO FORZA FUEL ECONOMY 10W-30 E6/E9 contributes to performance improvement and increase of oil-change intervals.
- Applications include on-highway transport vehicles operating at high speeds and high loads and off-highway vehicles and equipment operating at low speeds and high loads in applications in constructions, mining, shipping and agriculture.
- Meets the requirements of the specifications of all major European, American and Japanese manufacturers (OEM), it is thus suitable for mixed fleets of various manufacturers and technologies.

ADVANTAGES

EKO FORZA FUEL ECONOMY 10W-30 E6/E9 provides excellent wear protection and excellent oxidation resistance, as demonstrated by the results in critical tests of API CK-4, MB 228.51 and Volvo VDS-4.5 specifications:

- Provides 68% less wear of camshaft outlet in the OM646LA Cam Wear Outlet test, compared to the MB 228.51 limit.
- Provides 61% less wear of camshaft inlet in the OM646LA Cam Wear Inlet test, compared to the MB 228.51 limit.



PRODUCT DATA SHEET



ADVANTAGES

- Provides 60% less wear of cylinder in the OM646LA Cylinder Wear test, compared to the MB 228.51 limit.
- Provides 96% less increase in lubricant viscosity due to oxidation in the Mack T-13 KV40 increase test, compared to the Volvo VDS-4.5 limit.
- In the Mack T-13 Oxidation peak height test, provides 60% better protection against oxidation compared to the API CK-4 limit and 40% better protection compared to the Volvo VDS-4.5.
- Provides 26% less lubricant consumption in the Mack T-13 Average oil consumption test, compared to the Volvo VDS-4.5 limit.

TYPICAL CHARASTERISTICS

Properties	Methods	Units	EKO FORZA FUEL ECONOMY 10W-30 E6/E9
SAE Viscosity Grade	-	-	10W-30
Density, 15°C	ASTM D4052	g/ml	0.864
Kinematic viscosity, 100°C	ASTM D445	cSt	11.57
Kinematic viscosity, 40°C	ASTM D445	cSt	79.34
Viscosity index (VI)	ASTM D2270	-	138
CCS viscosity, -25°C	ASTM D5293	cP	5730
Sulfated ash	ASTM D874	% w/w	1.0
Base number, TBN	ASTM D2896	mg KOH/g	10.1
Pour Point	ASTM D5950	°C	-39
Flash Point	ASTM D92	°C	234

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.



PRODUCT DATA SHEET



SPECIAL INSTRUCTIONS

The lubricant recommendation for EURO 6 engines varies depending on the manufacturer. You should always consult the vehicle manual.

HEALTH AND SAFETY

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

Issue 2, 20 July 2020

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511 and +30 210 7725 418. Advice on safe handling is provided in the Safety Data Sheet.