

EKOGREASE Li-EP

Lithium grease with EP additives

Description

The EKOGREASE Li-EP range includes high quality lithium greases enhanced with extreme pressure (EP) additives.

EKOGREASE Li-EP range products provide excellent endurance at high temperatures and optimum pumpability at low temperatures.

Recommended operating temperature range is from -30°C to +130°C.

Specifications

DIN 51825 KP00K-30, KP0K-30, KP1K-30, KP2K-30, KP3K-30.

Applications

- EKOGREASE Li-EP 0 and EKOGREASE Li-EP 1 grease products are suitable for central lubrication systems and all operations requiring top low temperature performance.
- EKOGREASE Li-EP 2 is a multi-purpose grease.
- EKOGREASE Li-EP 3 is ideal for operations requiring high resistance to washout by water and optimal protection from dust.

Advantages

- Optimal resistance to heavy loads.
- Excellent lubrication and mechanical stability over a wide range of operating temperatures.
- High resistance to washout by water.
- Optimal protection against corrosion.
- Excellent pumpability at low temperatures.

Typical Characteristics

			EKOGREASE				
Properties	Methods	Units	Li-EP 00	Li-EP 0	Li-EP 1	Li-EP 2	Li-EP 3
Soap Base	-	-	Lithium				
Base Oil	-	-	Mineral Oil				
Colour	Visual Inspection	-	Amber				
NLGI	ASTM D217	-	00	0	1	2	3
Dropping Point	ASTM D2265	°C	175	180	190	190	195
Base Oil Viscosity at 40°C	ASTM D445	cSt	150	150	150	150	150
Worked Penetration, 60 strokes	ASTM D217	mm ⁻¹	400-430	355-385	310-340	265-295	220-250
Four ball weld load	ASTM D2596	Kg	250	250	250	250	250
Four ball test, LWI	ASTM D2596	kgf	45	45	45	45	45
Operating Temperature	-	°C	-30°C to +120°C	-30°C to +130°C			

Health and safety

Protect the environment while disposing of used product.