

# EKO GEAROL-1

## API GL-1 automotive gear oil

### Description

The EKO GEAROL-1 automotive gear oil series includes two gear oils with SAE 90 and SAE 85W-140 grades. EKO GEAROL-1 90 and EKO GEAROL-1 140 lubricants are suitable for gearboxes, differentials and other low-load gearwheel systems where manufacturer recommends a simple gear oil of API GL-1 quality.

EKO GEAROL-1 automotive gear oils should not be used in systems including hypoid gears, where gear oils with Extreme Pressure (EP) additives are required.

### Specifications

API GL-1

### Applications

- EKO GEAROL-1 90 and EKO GEAROL-1 140 lubricants are suitable for a variety of applications requiring API GL-1 quality level.
- Applications include manual transmissions in vehicles, farming and construction equipment and industrial applications, following manufacturer recommendation.

### Advantages

- High oxidative stability.
- Resistance to foaming.
- Good protection of metal accessories against corrosion.

## Typical Characteristics

Properties	Methods	Units	EKO GEAROL-1 90	EKO GEAROL-1 140
SAE Viscosity Grade	-	-	90	85W-140
Kinematic Viscosity, 100°C	ASTM D445	cSt	17.5	25
Viscosity Index (VI)	ASTM D2270	cSt	95	95
Pour Point	ASTM D5950	-	-18	-18
Flash Point, COC	ASTM D92	°C	236	246
Brookfield Viscosity, -12°C	ASTM D2983	cP	-	101500

## Health and safety

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.