

EKOGREASE EM 2

Lithium grease

Description

EKOGREASE EM 2 is a top quality, lithium-based grease, enhanced with antioxidants and corrosion inhibitors.

Specifications

DIN 51825 K2K-30.

Applications

- Meets all general lubrication needs of vehicles and machinery.
- Suitable for the lubrication of both plain and roller bearings in vehicles and equipment operating off road (construction, farming, mining, quarrying).
- Suitable for a vast array of industrial applications requiring lithium-based grease without EP additives.
- Ideal for the lubrication of roller bearings in electric motors.

Advantages

- Mechanical stability and resistance to shearing.
- Resistance to washout by water.
- Enhanced adhesion to metal surfaces.
- Excellent pumpability even at low temperatures.
- Optimal protection against corrosion.
- Effective performance over a wide temperature range (-30°C to +130°C).

Typical Characteristics

Properties	Methods	Units	EKOGREASE EM 2
Soap Base	-	-	Lithium
Base Oil	-	-	Mineral Oil
Colour	Visual Inspection	-	Amber
NLGI	ASTM D217	-	2
Dropping Point	ASTM D2265	°C	190
Base Oil Viscosity at 40°C	ASTM D445	cSt	110
Worked Penetration, 60 strokes	ASTM D217	mm ⁻¹	265-295
Operating Temperature	-	°C	-30°C to +130°C

Health and safety

Protect the environment while disposing of used product.

30 January 2025