

# EKO SLIDE

## Lubricants for machine tool slideways

### Description

The EKO SLIDE lubricant range includes lubricants for horizontal and vertical slideways of modern machine tools.

EKO SLIDE lubricants can also be used to lubricate gearboxes and hydraulic machine tool systems when the manufacturer recommends using one lubricant for all lubrication points of the machine tool.

### Specifications

DIN 51502 CG, CINCINNATI MILACRON.

### Advantages

- EKO SLIDE lubricants display excellent stick-slip performance. Stick-slip occurs in slow moving machines that operate under heavy loads; under such conditions the lubricating film breaks, and metal comes into contact with metal.
- They contain special adhesion additives which allow them to adhere firmly to the surfaces on which they slide preventing the metals from coming into direct contact.
- They easily separate from water-based cutting fluids.
- They provide excellent protection against wear and have excellent thermal stability and resistance to oxidation, thus meeting the performance requirements of both gear and hydraulic oils.

## Typical Characteristics

Properties	Methods	Units	EKO SLIDE 32	EKO SLIDE 68	EKO SLIDE 220
ISO Viscosity Grade	-	-	32	68	220
Density, 15°C	ASTM D4052	g/ml	0.872	0.886	0.895
Kinematic Viscosity, 40°C	ASTM D445	cSt	32	68	220
Kinematic Viscosity, 100°C	ASTM D445	cSt	5.4	8.7	18.7
Viscosity Index (VI)	ASTM D2270	-	100	98	95
Pour Point	ASTM D5950	°C	-21	-18	-15
Flash Point COC, min	ASTM D92	°C	215	220	235

## Health and safety

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

30 January 2025